KERN SXS6K-3M

Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]





Measuring system	
Adjustment options:	External calibration
Linearity:	1 g 2 g
Load cell connection:	6-wire
Readability [d]:	1 g 2 g
Recommended adjusting weight:	6 kg (M1)
Repeatability:	1 g 2 g
Resolution:	3 3.000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-6 kg
Warm up time:	10 min 10 min
Weighing capacity [Max]:	3 kg 6 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height (large): 5,500 cm

Technical data about verification		
Minimum load [Min]:	20 g 40 g	
Periodic Verification for Italy:	969-112	
Verification approval conforming to 2014/31/EU:	yes	
Verification by KERN possible:	yes	
Verification class:	III	
Verification value [e]:	1 g 2 g	

Counting	
Counting resolution:	30000
Mininum piece weight at piece counting (Laboratory:	200 mg
Mininum piece weight at piece counting (Normal):	2 g

Functions		
Counting function:	yes	
Data hold function:	yes	
Peak function:	yes	
PRE-TARE function:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	
Environmental conditions		
Maximum humidity:	80 %	

,	
Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter/adapter included:	EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional

 $40\,^{\circ}\text{C}$

-10 °C

(factory)

0%

Service

(WxDxH):

(WxDxH):

Dimensions of weighing plate

Adjustment at the location of installation: 961-248

Maximum operating temperature: Minimum ambient temperature:

Minimum humidity:

DAkkS Certificate: 963-128 Verification: 965-228

Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale

Floudel Gloup.	iliuusiilai scale
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	490 x 570 x 212 mm
Gross weight:	7 kg
Net weight:	5,100 kg
Shipping method:	Parcel service
Construction	
Cable length of display device:	2,500 m
Dimensions of display device	232 x 150 x 80 mm

300 x 240 x 86 mm

KERN SXS6K-3M



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes Wall mount: yes

Weighing surface (WxD): 300 x 240 mm

Piktogramme

STANDARD





















FACTORY









