

## technical data sheet

Order No.	484-1075
Item/Model	SARO Thermo Connect Kit + sensor model 4777
GTIN	4017337 058211



- Measuring unit for temperature and humidity consisting of sensor (B) and gateway (A)
- Measured values can be transferred to a smartphone (iOS / Android) or the PC
- Alarms can be activated in the event of set deviations
- Sensor range of approx. 100 m (radio frequency 868 MHz)
- Thanks to an internet connection, flexible data retrieval / control is possible everywhere
- Measuring range:
  - -5 / +59.9 °C (accuracy +/- 1 °C)
  - 5/95% RH (accuracy +/- 5%)
  - -50 / + 110 °C (probe) (accuracy +/- 0.5 °C))
- Scope of delivery:
  - Sensor with digital display and probe with 3 m long cable, including plastic wall bracket (Required batteries 2x AAA each 1.5 V not included)
  - contain)
  - Gateway with plastic wall bracket and 230 volt power adapter + 1.3 meter
  - Router connection cable
- There is no need to manually record values due to the automatically possible PDF / CSV report,
- Can be saved or printed out (can be accessed for up to 90 days)
- Easy installation of the free Thermoconnect app on your smartphone
- or via the free website: [monitor.mobile-alerts.eu](http://monitor.mobile-alerts.eu)
- Sensors (B) can be easily connected and controlled via QR code scanning and easy to configure on smartphones
- Expansion of up to 60 sensors possible
- (additional sensor: 1 piece - order no. : 484-1070)

Origin	China
customs tariff no.	9025190090
Importer	Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY