

technical data sheet

Order No. **496-1020**

Item/Model **SARO Refrigerated cabinet US 70**

GTIN **4017337063611**



- Material (inside/outside) stainless steel 304
- 1 door (W 690 x H 1675 mm), door hinge on the right - not interchangeable
- Door self-closing, not lockable (lock can be ordered as an option)
- Removable door seal for easy replacement/ cleaning
- The fan stops when the door is opened (energy saving)
- Inside rounded corners for easy cleaning (HACCP compliant)
- Insulation (housing) 70 mm, (bottom) 80 mm, polyurethane
- Automatic defrosting
- Ventilated refrigeration
- Digital temperature setting/control (DIXELL thermostat)
- Temperature range -1 to +10 °C
- Suitable for climate class 5 (ambient temperature 40 °C / 40% humidity -> powerful device!)
- Evaporator with special corrosion protection for storing salty foods, milk and cheese products
- LED interior lighting
- Connection: 220 - 240 V / 1 Ph. / 50 Hz / 0.45 kW
- 3 plastic-coated grids (W 550 x 630 mm)
- 3 pairs of runners as U-profile
- gross volume: 620 liters, net: 507 liters
- dimensions: W 700 x D 820 x H 2070 mm
- 4 height-adjustable stainless steel legs (H 100 to 130 mm)
- Net/gross weight: 115 kg / 125 kg
- Refrigerant R290/130g
- Energy efficiency class B (spectrum A+++ to E) at climate class 5!

Origin Griechenland
customs tariff no. 84181020
Dealer Saro Gastro-Products GmbH, Sandbahn 6, 46446 Emmerich am Rhein, GERMANY

Eingetragen: Kleve HRB 2768 * Geschäftsführer: Walter Spangenberg, Dominique de Charry, Aloys de Charry
ID-Nr. DE 120061194 * St.-Nr. 116/5718/0194 * ILN 4017337000005 * WEEE-Reg.-Nr. DE 58229827